

[+You](#) [Web](#) [Images](#) [Videos](#) [Maps](#) [News](#) [Shopping](#) [Email](#) [More](#)
[Sign in](#)[My Citations](#)

Google scholar

Search

[Advanced Scholar Search](#)

Scholar

Articles and patents

anytime

include citations

[Create email alert](#)

Results 1 - 10 of about 6,040. (0.05 sec)

Virtualizing serial bus information point by address mapping via a parallel port

DG Ellis... - US Patent 6,119,195, 2000 - Google Patents

... 430 420 TRANSMITTER PROCESSOR' REGISTER 410 -4- 4J4 r CRC GENERATOR DATA MUX  
 CONSTANT -416 230 ~^^~USB TRANSMITTER PID ADR ENDP ... 3 512 510 \ EP1 COMPARE  
 CIRCUIT ADR EP1 FIFO IK X 8 OUT WE IN 514 -4 EPI ADDRESS GENERATOR IF IN ...

[Cited by 11](#) - [Related articles](#) - [All 2 versions](#)System and method for reducing power consumption in a universal serial bus device

DG Wright, TJ Williams - US Patent 6,816,976, 2004 - Google Patents

... US Patent Nov. 9, 2004 Sheet 4 of 5 US 6,816,976 B2 SYNC PID ADDRESS CRC SYNC PID  
 DATA CRC SYNC PID FIG. ... 15. The apparatus according to claim 14, wherein said device is further  
 configured to **determine** an **address** of said particular type of packet. 60 16. ...

[Cited by 13](#) - [Related articles](#) - [All 3 versions](#)Idle period signalling in a packet switching system

ML Larson, AA Robrock... - US Patent 4,646,287, 1987 - Google Patents

... The detector identifies **idle** packets by their **PID** field and discards them—blocks them from ... TRUNK  
 CONTROLLER MEMORY ADDRESS BUS 1417 1418 FROM/TO SWITCH NETWORK 116  
 SWITCH ... For example, a re-ceiving node cannot **determine** from receipt of **idle** code ...

[Cited by 66](#) - [Related articles](#) - [All 2 versions](#)Personal mobility and communication termination for users operating in a plurality of heterogeneous networks

HC Lee, KK Basu, SH Zhou, W Yuan... - US Patent ..., 2000 - Google Patents

... Particularly, if an immediate conversation is required, it is difficult to **determine** a par- ticular  
 number to dial or **address** to employ to immediately reach the user. ... However, if Tom Jones does  
 not have an email **address**, his **PID** could be his phone number, (972) 684-0800. ...

[Cited by 154](#) - [Related articles](#) - [All 2 versions](#)Communication control apparatus for common bus connection devices

M Motomura... - US Patent 7,779,195, 2010 - Google Patents

... bus to the com- mon bus, and an access suspend unit configured to **determine** that another ... in  
 the device in question when the input determination unit determines that the **address** of the ... 2bit  
 EOP CRC16 DATA PID SYNC 16 HANDSHAKE PACKET Sbit Sbit SYNC PID 2bit EOP ...

[Related articles](#) - [All 4 versions](#)Method and apparatus for a Gigabit Ethernet MAC (GMAC)

V Hunter - US Patent 6,366,557, 2002 - Google Patents

... processing may include performing Layer 2, eg, Media Access Control (MAC) layer, or Layer  
 3, eg, Net- work layer, **address** look-up to **determine** the forwarding control information such as,  
 the destination **address** (eg, a multicast **address** or egress **PID** and egress ...

[Cited by 33](#) - [Related articles](#) - [All 2 versions](#)Early availability of forwarding control information

M Momirov - US Patent 6,320,859, 2001 - Google Patents

... Access Control (MAC) layer, or Layer 3, eg, Net- 10 work layer, **address** look-up to **determine**  
 the forwarding ... or not the cell is to be forwarded from the output queue to a single **PID** (eg, in ... When  
 the cell is part of a unicast packet, the destination **address** may be represented by a ...

[Cited by 49](#) - [Related articles](#) - [All 2 versions](#)System, apparatus and method for performing look-ahead lookup on predictive information in a cache memory

ZS Hakura, R Danilak, BW Simeral... - US Patent ..., 2007 - Google Patents

... Arbiter 118 is configured to **determine** which prediction of the generated predictions is to ... ciated  
 therewith can include a prediction identifier ("PID") 20 and a corresponding target **address**. A  
**PID** (not shown) identifies the trigger **address** (or a representation thereof) that caused ...

[Related articles](#) - [All 4 versions](#)Address routing using address-sensitive mask decimation scheme

VA Hunter... - US Patent 6,223,172, 2001 - Google Patents

... search. A mask is applied to an **address**, such as a destination Internet Protocol (IP)  
**address**, to **determine** a masked **address** that is to be used for purposes of locating  
 a matching entry in the forwarding database. The forwarding ...

[Cited by 53](#) - [Related articles](#) - [All 3 versions](#)Effects of wi-fi and bluetooth battery exhaustion attacks on mobile devicesBR Meyers, JP Dunning... - ... (HICSS), 2010 43rd ..., 2010 - [ieeeexplore.ieee.org](#)

... The **PID** chosen for all attack testing purposes was based on random selection prior to device ...  
 in Table 5: • Ping Flood: Ping is a troubleshooting network tool used to **determine** if a ... was launched  
 at PDA 1 using Backtrack 3 and the command: hping3 --faster <PDA1 IP Address>. ...

[Cited by 3](#) - [Related articles](#) - [All 3 versions](#)[Create email alert](#)

Result Page: 1 2 3 4 5 6 7 8 9 10 **Next**

determine the address of PID and idle

[About Google Scholar](#) - [About Google](#) - [My Citations](#)

©2011 Google